

## PRODUCT SPECIFICATION

THE GOODYEAR TIRE & RUBBER CO.
GOODYEAR CHEMICAL AKRON, OH 44306-3299
USA: 1-800-548-8107

## *NATSYN 2200*

Description: NATSYN 2200 is a high cis (98.5% Typical) polyisoprene containing a nonstaining

FDA-regulated antioxidant.

It is packaged as 34 kg (75 pound) bales.

| PROPERTY                 | LIMITS                                      | TEST<br>METHOD |
|--------------------------|---|----------------|
| Appearance               | Opaque white to translucent light gray bale | Visual         |
| Volatile matter, %       | <= 0.5                                      | ASTM D 5668    |
| Ash, %                   | <= 0.6                                      | ASTM D 5667    |
| Extractables, %          | <= 3.0                                      | ASTM D 5774    |
| Mooney, ML-4' @ 100 C    | 80 +/- 10                                   | ASTM D 1646    |
|                          | FleXi                                       | lis            |
| STRESS/STRAIN PROPERTIES | PVT. LTD.<br>LET'S GO. LET'S GROW           |                |

| SS Description: 40 Min @ 135 C Cure | Typical Values |       |
|-------------------------------------|----------------|-------|
| ASTM Ref #: 412                     | Midpoint       | Range |
| 300% Modulus, MPa                   | +/-            | to    |
| Tensile, MPa, minimum               | +/-            | to    |
| Elongation, %                       | +/-            | to    |

This product should be stored in its original packaging in a dry atmosphere away from heat and ultraviolet light

As a guideline , NATSYN 2200 should be re-tested every 18 months following the date of manufacture . The most appropriate test would be Mooney .

Goodyear test methods are available upon request .

Check with your Goodyear salesperson to confirm the revision number of the most recent specification  $\,$  .

CD-PS-0013; Rev: 4 - NATSYN 2200

Print Date: 04/18/2013



CD-PS-0013; Rev: 4 - NATSYN 2200 Print Date: 04/18/2013